

Translation Management Services

Reviewed by: CR/ES
 For Client: Preval
 Date assigned: 1/2/13

Client Job No/PO No:
 Delivery Date: 1/14/13

TMS Job#1212010
 Contact: Eileen Giuffre
 Page 1 of 2

ENGLISH	ITALIAN <i>(For easy cut and paste into your layouts, use your cursor as an arrow to highlight the entire cell. Then, while holding shift, press the back arrow to highlight just the text desired.)</i>
268_PowerUnit.ai	
<p>ATOMIZES UP TO 16 OZ</p> <p>This package includes a Power Unit and a diptube.</p>	<p>NEBULIZZA FINO A 473 MILLILITRI</p> <p>La confezione include un'unità di erogazione e un tubetto di pescaggio.</p>
<p>5 STEP QUICK START</p> <ol style="list-style-type: none"> 1. Insert the diptube into the bottom of the Power Unit. 2. Remove bottom strainer prior to spraying any thick paint(s) or coating(s). 3. Test spray Power Unit by using water or solvents prior to spraying intended application(s). 4. Attach Power Unit to the Preval Product Container (not included). Don't shake. 5. Spray. Allow sufficient time for paint or liquid to pull up the diptube. 	<p>AVVIO RAPIDO IN 5 FASI</p> <ol style="list-style-type: none"> 1. Inserire il tubetto di pescaggio nella parte inferiore dell'unità di erogazione. 2. Rimuovere il filtro dalla parte inferiore prima di erogare rivestimenti o vernici dense. 3. Provare l'unità di erogazione usando acqua o solventi prima di erogare il prodotto desiderato. 4. Fissare l'unità di erogazione al serbatoio del prodotto Preval (non incluso). Non agitare. 5. Erogare il prodotto. Tenere presente che trascorre un certo tempo prima che la vernice o il liquido inizi a fluire lungo il tubetto di pescaggio.
MANUFACTURED IN THE USA	FABBRICATO NEGLI USA
<p>REPLACEMENT POWER UNIT</p> <p>THIS REPLACEMENT POWER UNIT IS DESIGNED TO REPLACE THE POWER UNIT IN YOUR PREVAL SPRAY SYSTEM.</p>	<p>UNITÀ DI EROGAZIONE DI RICAMBIO</p> <p>QUESTA UNITÀ DI EROGAZIONE DI RICAMBIO È CONCEPITA PER SOSTITUIRE L'UNITÀ DI EROGAZIONE DEL SISTEMA A SPRUZZO PREVAL.</p>
<p>WARNING! FLAMMABLE.</p> <p>Contents Under Pressure. Deliberate or intentional misuse by</p>	<p>ATTENZIONE. INFIAMMABILE.</p> <p>Il contenuto è sotto pressione. L'abuso deliberato o</p>

268_PowerUnit.ai

PREV 268 PowerUnit ITAL TMS.doc

Translation Management Services

Reviewed by: CR/ES
For Client: Preval
Date assigned: 1/2/13

Client Job No/PO No:
Delivery Date: 1/14/13

TMS Job#1212010
Contact: Eileen Giuffre
Page 2 of 2

<p>inhaling vapors may be harmful or fatal. Do not puncture or incinerate container. Do not expose to heat, sparks or open flame or store at temperature in excess of 120° F (49° C). This is not a toy. Keep out of reach of children. Do not use with foods, pharmaceuticals or personal products.</p>	<p>intenzionale inalando vapori può essere pericoloso o letale. Non perforare né bruciare il contenitore. Non esporre a fonti di calore, scintille o fiamme libere né riporre a temperature superiori a 49 °C. Questo prodotto non è un giocattolo. Tenere fuori della portata dei bambini. Non utilizzare con alimenti, prodotti farmaceutici o personali.</p>
<p>WARNING! FLAMMABLE. CONTENTS UNDER PRESSURE. Read carefully precautions on side panels.</p> <p>NET WT 1.94 OZ (55g)</p>	<p>ATTENZIONE. INFIAMMABILE. CONTENUTO SOTTO PRESSIONE. Leggere attentamente le precauzioni riportate sui pannelli laterali.</p> <p>PESO NETTO 55 g</p>