

## Translation Management Services

Reviewed by: MTM/ES  
 For Client: Preval  
 Date assigned: 1/2/13

Client Job No/PO No:  
 Delivery Date: 1/14/13

TMS Job#1212010  
 Contact: Eileen Giuffre  
 Page 1 of 2

| ENGLISH   | MALAY<br><i>(For easy cut and paste into your layouts, use your cursor as an arrow to highlight the entire cell. Then, while holding shift, press the back arrow to highlight just the text desired.)</i>   |
|---|---|
| <b>268_PowerUnit.ai</b>   |   |
| ATOMIZES UP TO 16 OZ<br><br>This package includes a Power Unit and a diptube.   | MENYEMBUR SEHINGGA 16 AUNS<br><br>Kotak ini mengandungi Unit Tenaga dan tiub celup.   |
| 5 STEP QUICK START<br><br><ol style="list-style-type: none"> <li>1. Insert the diptube into the bottom of the Power Unit.</li> <li>2. Remove bottom strainer prior to spraying any thick paint(s) or coating(s).</li> <li>3. Test spray Power Unit by using water or solvents prior to spraying intended application(s).</li> <li>4. Attach Power Unit to the Preval Product Container (not included). Don't shake.</li> <li>5. Spray. Allow sufficient time for paint or liquid to pull up the diptube.</li> </ol> | PERMULAAN PANTAS 5 LANGKAH<br><br><ol style="list-style-type: none"> <li>1. Masukkan tiub celup di hujung Unit Tenaga.</li> <li>2. Keluarkan penapis bawah sebelum menyembur sebarang cat atau lapisan yang pekat.</li> <li>3. Uji sembur Unit Tenaga dengan menggunakan air atau pelarut sebelum menyembur cat atau lapisan yang dirancang.</li> <li>4. Pasangkan Unit Tenaga pada Bekas Produk Preval (tidak disertakan). Jangan goncang.</li> <li>5. Sembur. Berikan masa yang mencukupi untuk cat atau cecair mengalir naik ke dalam tiub celup.</li> </ol> |
| MANUFACTURED IN THE USA   | DIKILANGKAN DI AMERIKA SYARIKAT   |
| REPLACEMENT POWER UNIT<br><br>THIS REPLACEMENT POWER UNIT IS DESIGNED TO REPLACE THE POWER UNIT IN YOUR PREVAL SPRAY SYSTEM.  | UNIT TENAGA GANTI<br><br>UNIT TENAGA GANTI INI BERTUJUAN UNTUK MENGGANTIKAN UNIT TENAGA DALAM SISTEM SEMBURAN PREVAL ANDA.  |
| WARNING! FLAMMABLE.<br>Contents Under Pressure. Deliberate or intentional misuse by inhaling vapors may be harmful or fatal. Do not puncture or incinerate container. Do not expose to heat, sparks or open flame or store at temperature in excess of 120° F (49° C).  | AMARAN! MUDAH TERBAKAR.<br>Kandungan Di Bawah Tekanan. Salah guna secara sengaja dengan menyedut wasap mungkin memudaratkan atau membawa maut. Jangan tebuk atau bakar bekas. Jangan dedahkan kepada haba, percikan api atau nyalaan terbuka,   |

## Translation Management Services

Reviewed by: MTM/ES  
For Client: Preval  
Date assigned: 1/2/13

Client Job No/PO No:  
Delivery Date: 1/14/13

TMS Job#1212010  
Contact: Eileen Giuffre  
Page 2 of 2

|  |   |
|--|---|
| This is not a toy. Keep out of reach of children. Do not use with foods, pharmaceuticals or personal products. | atau menyimpannya pada suhu melebihi 120°F (49°C). Ini bukan mainan. Jauhkan daripada kanak-kanak. Jangan gunakan bersama-sama makanan, ubat-ubatan atau produk peribadi. |
| WARNING! FLAMMABLE.<br>CONTENTS UNDER PRESSURE.<br>Read carefully precautions on side panels.                  | AMARAN! MUDAH TERBAKAR.<br>KANDUNGAN DI BAWAH TEKANAN.<br>Baca langkah beringat-ingat dengan teliti di panel sebelah.   |
| NET WT 1.94 OZ (55g)   | BERAT BERSIH 1.94 OZ (55g)  |
|  |   |
|  |   |